



CODING TABLE

IAC LOC RWY 13					BELO HORIZONTE / Pampulha – Carlos Drummond de Andrade (SBBH)							SBBH_IAC_01H		25 FEB 21	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N	N/A	PUMAT	IF	N/A	N/A	N/A	+7000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N	IPM	IVSAM	CF	133.76° Mag / 110.82° True	N/A	N/A	+5700	N/A	N/A	6.8	N/A	IF	N/A
10	APCH	N	N/A	ERVIM	IF	N/A	N/A	N/A	+7000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N	CNF	IVSAM	CF	41.69° Mag / 18.75° True	N/A	N/A	+5700	N/A	N/A	6.0	N/A	IF	N/A
10	FINAL	N	N/A	IVSAM	CF	N/A	N/A	N/A	+5700	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N	IPM	POPRI	IF	133.79° Mag / 110.82° True	N/A	N/A	+4500	N/A	N/A	5.2	N/A	FAF	N/A
30	FINAL	N	IPM	BH008*	CF	133.76° Mag / 110.76° True	N/A	N/A	R3746	N/A	N/A	2.0	-3.5	SDF	N/A
40	FINAL	Y	IPM	RWY13	IF	133.75° Mag / 110.76° True	N/A	N/A	@2631	N/A	N/A	3.0	-3.5	MAPT	N/A
10	MA	N	BHZ	OPSAB	CF	133.73° Mag / 110.62° True	N/A	N/A	+8000	N/A	N/A	22.8	N/A	MAHF	N/A
20	MA	Y	BHZ	OPSAB	HM	133.73° Mag / 110.62° True	L	N/A	+8000	N/A	N/A	1.00 min	N/A	MAHF	N/A

(*) Fictitious point only for coding purpose.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
POPRI	S 19:49:01.50 / W 44:02:38.09
RWY13	S 19:50:48.36 / W 43:57:40.47
IVSAM	S 19:47:09.86 / W 44:07:48.46
PUMAT	S 19:44:44.40 / W 44:14:32.40
ERVIM	S 19:52:52.20 / W 44:09:51.60
OPSAB	S 19:59:23.87 / W 43:33:37.60
IPM	S 19:51:19.50 / W 43:56:13.70
CNF	S 19:33:29.57 / W 44:02:54.65
BHZ	S 19:50:08.77 / W 44:00:12.82
BH008*	S 19:49:45.04 / W 44:00:36.86

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT