



CODING TABLE

RNP Y RWY 24					MACAÉ / Macaé (SBME)							SBME_IAC_001		25 FEB 21	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	ME042	IF	N/A	N/A	N/A	+3000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	ME043	TF	306.90° Mag / 283.39° True	N/A	N/A	+2000	N/A	N/A	6.00	N/A	IF	RNP APCH
10	APCH	N/A	N/A	ME041	IF	N/A	N/A	N/A	+3000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	ME043	TF	236.89° Mag / 213.37° True	N/A	N/A	+2000	N/A	N/A	6.00	N/A	IF	RNP APCH
10	FINAL	N/A	N/A	ME043	IF	N/A	N/A	N/A	+2000	N/A	N/A	N/A	N/A	IF	RNP APCH
20	FINAL	N	N/A	ME044	TF	236.86° Mag / 213.37° True	N/A	N/A	R1650	N/A	N/A	5.00	N/A	FAF	RNP APCH
30	FINAL	N	N/A	*MCA04	TF	236.82° Mag / 213.34° True	N/A	N/A	R854	N/A	N/A	2.50	-3.00	SDF	RNP APCH
40	FINAL	Y	N/A	RWY24	TF	236.86° Mag / 213.39° True	N/A	N/A	@58	N/A	N/A	2.50	-3.00	LTP/FTP	RNP APCH
10	MA	N/A	N/A	N/A	VA	236.85° Mag / 213.38° True	N/A	N/A	+1500	N/A	N/A	N/A	N/A	N/A	RNP APCH
20	MA	Y	N/A	ME042	DF	N/A	L	N/A	+3000	N/A	N/A	N/A	N/A	MAHF	RNP APCH
30	MA	Y	N/A	ME042	HM	306.90° Mag / 283.36° True	R	N/A	+3000	N/A	N/A	1.00 min	N/A	MAHF	RNP APCH

*Fictitious point. Only for coding purpose.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
ME041	S 22:06:53.84W 41:36:17.30
ME042	S 22:13:19.11W 41:33:33.11
ME043	S 22:11:55.57W 41:39:50.57
ME044	S 22:16:07.02W 41:42:48.38
*MCA04	S 22:18:12.78W 41:44:17.26
RWY24	S 22:20:18.47W 41:45:46.27

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT