

INSTRUMENT APPROACH CHART (IAC)

PORTO VELHO / Gov. Jorge Teixeira de Oliveira, INTL (SBPV)

AD ELEV: 295'

RNAV (GNSS) Z RWY 01



D-ATIS	APP PORTO VELHO 120.25 120.80		TWR PORTO VELHO 118.20 118.55 121.50		GNDC NIL
N/A	FINAL CRS 010°	FAF 1930'	LNAV/VNAV DA / (OCH): 660' / (373')		LNAV MDA / (OCH): 780' / (490')

APCH Perdida: Subir para **3000'** no rumo **010** para espera em PV003.

Missed APCH: Climb to **3000'** on course **010** for holding over PV003.

RMK: 1) Para sistemas não compensados Baro-VNAV, LNAV/VNAV NAO AUTORIZADO abaixo de 0°C ou acima de 50°C.

1) For uncompensated systems Baro-VNAV, LNAV/VNAV NOT AUTHORIZED below 0°C or above 50°C.



RWY01	1.4	2.2	3.0	4.0	PV378		KT	090	110	130	150	170	190
ALT	780	1037	1292	1611	1930		FPM	500	600	700	800	900	1000
(HGT)	490	750	1005	1324	1643		FAF-MAPT	NA					

STRAIGHT-IN	CAT	A	B	C	D	E
	DA / (OCH)	660' / (373')				
LNAV/VNAV	ALS/NO ALS/ RVR ALS (m)	NIL / 1600 / NIL		NIL / 1700 / NIL		NA
	MDA / (OCH)	780' / (490')				
LNAV	ALS/NO ALS/RVR ALS (m)	NIL / 1600 / NIL		NIL / 2300 / NIL		
	MDA / (OCH)	NA				
CIRCLING	MDA / (OCH)	NA				
	VIS (m)					

CHANGES: FREQ.