



CODING TABLE

IAC ILS Y RWY09					MANAUS / Ponta Pelada, MIL (SBMN)							SBMN_IAC_01N		31 DEC 20	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST	VA (°)	Role Of TheFix	Navigation Specification
10	APCH	N/A	N/A	VURIV	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	MN009	TF	21.75° Mag 6.05° True	N/A	N/A	+2400	N/A	N/A	6.42	N/A	IF	RNP APCH
10	APCH	N/A	N/A	ARSOS	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	MN009	TF	140.64° Mag 124.93° True	N/A	N/A	+2400	N/A	N/A	5.21	N/A	IF	RNP APCH
10	FINAL	N/A	N/A	MN009	IF	N/A	N/A	N/A	+2400	N/A	N/A	N/A	N/A	IF	RNP APCH
20	FINAL	N	LOC/DME IPE	MN011	TF	91.83° Mag 76.08° True	N/A	N/A	R1920	N/A	N/A	5.00	N/A	FAF	RNP APCH
30	FINAL	Y	LOC/DME IPE	RWY09*	CF	91.87° Mag 76.08° True	N/A	N/A	@298	N/A	N/A	5.00	-3.00	LTP	N/A
10	MA	N/A	N/A	N/A	VA	91.87° Mag 76.08° True	N/A	N/A	+2000	250	-	N/A	+2.30	N/A	N/A
20	MA	Y	N/A	GELAG	DF	N/A	R	N/A	+4000	250	-	N/A	+2.30	MAHF	RNP APCH
30	MA	Y	N/A	GELAG	HM	271.87° Mag 255.96° True	L	N/A	+4000	N/A	N/A	1.00 min	N/A	MAHF	RNP APCH

*Fictitious point = for coding purpose only.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
MN009	S 03:11:19.15W 60:09:27.04
MN011	S 03:10:06.65W 60:04:35.92
RWY09	S 03:08:54.12W 59:59:44.83
GELAG	S 03:12:02.48W 59:47:28.01
VURIV	S 03:17:43.94W 60:10:07.61
ARSOS	S 03:08:19.25W 60:13:43.26
IPE	S 03:08:36.46W 59:58:33.90

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT