



CODING TABLE

IAC ILS M OR LOC M RWY 27L					SÃO PAULO / Guarulhos – Gov. André Franco Montoro, INTL (SBGR)							SBGR_IAC_01C		18 JUN 20	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	VURAK	IF	N/A	N/A	N/A	+7000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	IBC	ESDAR	CF	273.44° Mag 251.68° True	N/A	N/A	+5500	N/A	N/A	6.06	N/A	IF	N/A
10	APCH	N/A	N/A	ANSUG	IF	N/A	N/A	N/A	+7000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	BCO	GR303*	AF	N/A	R	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	N/A
30	APCH	N/A	IBC	ESDAR	CF	273.44° Mag 251.68° True	N/A	N/A	+5500	N/A	N/A	3.64	N/A	IF	N/A
10	FINAL	N/A	N/A	ESDAR	IF	N/A	N/A	N/A	+5500	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	IBC	GR041	CF	275.35° Mag 253.65° True	N/A	N/A	R4090	N/A	N/A	5.66	N/A	FAF	N/A
30	FINAL	N/A	IBC	GR093*	CF	275.35° Mag 253.66° True	N/A	N/A	+3453	N/A	N/A	2.00	-3.00	SDF	N/A
40	FINAL	N/A	IBC	GR304*	CF	275.33° Mag 253.67° True	N/A	N/A	@2501	N/A	N/A	3.00	-3.00	LTP/FTP	N/A
10	MA	N/A	N/A	N/A	VA	275.34° Mag 253.68° True	N/A	N/A	+3400	230	-	N/A	2.86	N/A	N/A
20	MA	N/A	CGO	ISIMU	CF	90.78° Mag 69.78° True	L	N/A	+7000	230	-	N/A	N/A	MAHF	N/A
30	MA	N/A	CGO	ISIMU	HM	90.78° Mag 69.78° True	R	N/A	+7000	N/A	N/A	N/A	N/A	MAHF	N/A

(*) Fictitious point = for coding purpose only.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
ANSUG	S 23:16:25.75W 46:16:30.86
ESDAR	S 23:22:51.60W 46:16:24.60
ISIMU	S 23:31:14.03W 46:20:19.45
VURAK	S 23:20:56.81W 46:10:09.57
GR041	S 23:24:27.61W 46:22:18.87
GR303	S 23:21:42.71W 46:12:39.43
GR093	S 23:25:01.50W 46:24:24.06
GR304	S 23:25:52.26W 46:27:31.89

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT