



CODING TABLE

IAC ILS U (Converging) RWY 28					RIO DE JANEIRO / Galeão - Antônio Carlos Jobim, INTL (SBGL)							SBGL_IAC_02K		03 DEC 20	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	SEDBU	IF	N/A	N/A	N/A	+5000	N/A	N/A	N/A	N/A	IAF	RNAV 1 or RNP 1
20	APCH	N	N/A	LIXUG	TF	187.55° Mag 164.51° True	N/A	N/A	+2800	N/A	N/A	5.50	N/A	IF	RNAV 1 or RNP 1
10	APCH	N/A	N/A	KETUX	IF	N/A	N/A	N/A	+5000	N/A	N/A	N/A	N/A	IAF	RNAV 1 or RNP 1
20	APCH	N	N/A	LIXUG	TF	277.18° Mag 254.14° True	N/A	N/A	+2800	N/A	N/A	5.54	N/A	IF	RNAV 1 or RNP 1
10	FINAL	N/A	N/A	LIXUG	IF	N/A	N/A	N/A	+2800	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	ILM	VUBOP	CF	277.58° Mag 254.56° True	N/A	N/A	R1680	N/A	N/A	5.00	N/A	FAF	N/A
30	FINAL	N/A	ILM	ILM01*	CF	277.58° Mag 254.60° True	N/A	N/A	@80	N/A	N/A	5.01	-3.00	LTP/FTP	N/A
10	MA	N	N/A	GL086	DF	N/A	R	-4000	N/A	210	-	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	MA	N	N/A	GL087	TF	97.20° Mag / 74.15° True	N/A	N/A	N/A	210	-	5.54	N/A	OTHER	RNAV 1 or RNP 1
30	MA	Y	N/A	KETUX	TF	187.68° Mag / 164.60° True	R	N/A	+5000	210	-	7.50	N/A	MAHF	RNAV 1 or RNP 1
40	MA	Y	N/A	KETUX	HM	277.18° Mag / 254.10° True	L	N/A	+5000	N/A	N/A	N/A	N/A	MAHF	RNAV 1 or RNP 1

(*) Fictitious point = for coding purpose only.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
LIXUG	S 22:44:51.60W 43:02:37.20
VUBOP	S 22:46:11.88W 43:07:50.07
ILM01	S 22:47:32.03W 43:13:03.44
SEDBU	S 22:39:32.41W 43:04:12.51
KETUX	S 22:43:20.40W 42:56:51.60
GL086	S 22:37:36.12W 43:04:46.18
GL087	S 22:36:05.00W 42:59:00.86

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE