



CODING TABLE

RNAV (GNSS) Z (Converging) RWY 28					RIO DE JANEIRO / Galeão - Antônio Carlos Jobim, INTL (SBGL)							SBGL_IAC_04R		03 DEC 20	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	KETUX	IF	N/A	N/A	N/A	+5000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	LIXUG	TF	277.18° Mag 254.14° True	N/A	N/A	+2800	N/A	N/A	5.54	N/A	IF	RNP APCH
10	APCH	N/A	N/A	SEDBU	IF	N/A	N/A	N/A	+5000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	APCH	N	N/A	LIXUG	TF	187.55° Mag 164.51° True	N/A	N/A	+2800	N/A	N/A	5.50	N/A	IF	RNP APCH
10	FINAL	N/A	N/A	LIXUG	IF	N/A	N/A	N/A	+2800	N/A	N/A	N/A	N/A	IF	RNP APCH
20	FINAL	N	N/A	VUBOP	TF	277.56° Mag 254.55° True	N/A	N/A	R1670	N/A	N/A	5.00	N/A	FAF	RNP APCH
30	FINAL	Y	N/A	RWY28	TF	277.61° Mag 254.63° True	N/A	N/A	@78	N/A	N/A	5.01	-3.00	LTP/FTP	RNP APCH
10	MA	N	N/A	GL086	DF	N/A	R	-4000	N/A	210.	-	N/A	N/A	OTHER	RNP APCH
20	MA	N	N/A	GL087	TF	97.70° Mag / 74.15° True	N/A	N/A	N/A	210	-	5.54	N/A	OTHER	RNP APCH
30	MA	Y	N/A	KETUX	TF	187.68° Mag / 164.60° True	R	N/A	+5000	210	-	7.50	N/A	MAHF	RNP APCH
40	MA	Y	N/A	KETUX	HM	277.18° Mag / 254.914° True	L	N/A	+5000	N/A	N/A	N/A	N/A	MAHF	RNP APCH

(*) Fictitious point = for coding purpose only.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
LIXUG	S 22:44:51.60W 43:02:37.20
VUBOP	S 22:46:11.88W 43:07:50.07
RWY28	S 22:47:31.83W 43:13:03.52
KETUX	S 22:43:20.40W 42:56:51.60
SEDBU	S 22:39:32.41W 43:04:12.51
GL086	S 22:37:36.12W 43:04:46.18
GL087	S 22:36:05.00W 42:59:00.86

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE