



CODING TABLE

IAC VOR RWY 26					TAUBATÉ / Base de Aviação de Taubaté, MIL (SBTA)							SBTA_IAC_00N		10 SEP 20	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	DILUD	IF	N/A	N/A	N/A	+6000	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	N/A	ASETU	AF	N/A	R	N/A	+4600	N/A	N/A	N/A	N/A	IF	N/A
10	FINAL	N/A	N/A	ASETU	IF	N/A	N/A	N/A	+4600	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	TAU	TAU03	CF	270.55° Mag 248.40° True	N/A	N/A	+3900	N/A	N/A	1.50	N/A	SDF	N/A
30	FINAL	N/A	TAU	NEPER	CF	270.55° Mag 248.41° True	N/A	N/A	R3190	N/A	N/A	1.50	N/A	FAF	N/A
40	FINAL	N/A	TAU	TAU01	CF	270.55° Mag 248.42° True	N/A	N/A	R2556	N/A	N/A	1.50	-4.00	SDF	N/A
50	FINAL	N/A	TAU	TAU02*	CF	270.55° Mag 248.42° True	N/A	N/A	@1918	N/A	N/A	1.50	-4.00	FTP	N/A
10	MA	N/A	TAU	N/A	CA	270.55° Mag 248.43° True	N/A	N/A	+3000	N/A	N/A	N/A	N/A	OTHER	N/A
20	MA	N/A	TAU	DILUD	CF	50.99° Mag 28.83° True	R	N/A	+6000	N/A	N/A	N/A	N/A	MAHF	N/A
30	MA	N/A	TAU	DILUD	HM	230.99° Mag 208.83° True	R	N/A	+6000	N/A	N/A	1.00 min	N/A	MAHF	N/A

(*) Fictitious point only for coding purpose.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
ASETU	S 22:59:53.56W 45:24:36.70
TAU03	S 23:00:26.82W 45:26:07.39
NEPER	S 23:01:00.06W 45:27:38.09
TAU01	S 23:01:33.29W 45:29:08.81
TAU02	S 23:02:06.51W 45:30:39.54
DILUD	S 22:56:47.27W 45:27:34.01

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT