



## CODING TABLE

IAC ILS N RWY27L					SÃO PAULO / Guarulhos - Gov. André Franco Montoro, INTL (SBGR)							SBGR_IAC_00X		10 SEP 20	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST NM	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	ANSUG	IF	N/A	N/A	N/A	+7000	230	-	N/A	N/A	IAF	RNAV 1 / RNP 1
20	APCH	N	N/A	ESDAR	TF	200.90° Mag 179.14° True	N/A	N/A	+5500	N/A	N/A	6.41	N/A	IF	RNAV 1 / RNP 1
10	APCH	N/A	N/A	VURAK	IF	N/A	N/A	N/A	+7000	N/A	N/A	N/A	N/A	IAF	RNAV 1 / RNP 1
20	APCH	N	N/A	ESDAR	TF	273.42° Mag 251.68° True	N/A	N/A	+5500	N/A	N/A	6.06	N/A	IF	RNAV 1 / RNP 1
10	FINAL	N/A	N/A	ESDAR	IF	N/A	N/A	N/A	+5500	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	Y	IBC	GR041	CF	275.34° Mag 253.60° True	N/A	N/A	R4090	N/A	N/A	5.66	N/A	FAF	N/A
30	FINAL	Y	IBC	RW27L	CF	275.33° Mag 253.68° True	N/A	N/A	@2501	N/A	N/A	5.0	-3.00	LTP/FTP	N/A
10	MA	N/A	N/A	N/A	VA	275.32° Mag 253.66° True	N/A	N/A	+3400	230	-	N/A	2.86	N/A	RNAV 1 / RNP 1
20	MA	Y	N/A	ISIMU	DF	N/A	L	N/A	+6000	230	-	N/A	2.86	MAHF	RNAV 1 / RNP 1
30	MA	Y	N/A	ISIMU	HM	130.00° Mag 108.31° True	R	N/A	+6000	N/A	N/A	1.00 min	N/A	MAHF	RNAV 1 / RNP 1

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
IBC	S 23:26:22.65W 46:29:24.34
ESDAR	S 23:22:51.60W 46:16:24.60
GR041	S 23:24:27.61W 46:22:18.87
ISIMU	S 23:31:14.03W 46:20:19.45
ANSUG	S 23:16:25.75W 46:16:30.86
VURAK	S 23:20:56.81W 46:10:09.57
RW27L	S 23:25:52.28W 46:27:31.88

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT